



SMALL CASES

EXTERIOR DIMENSIONS

INTERIOR DIMENSIONS

LID/BOTTOM DEPTH

WEIGHT

COLORS

AVAILABLE ACCESSORIES

CERTIFICATES

[LINK >](#)



> Shown with panel frame option for special application usage.

1150 CASE

9.12" x 7.56" x 4.37"
(23.2 x 19.2 x 11.1 cm)

8.18" x 5.68" x 3.62"
(20.8 x 14.4 x 9.2 cm)

0.75" / 2.87"
(1.9 cm / 7.3 cm)

1.98 lbs. (0.9 kg) WITH FOAM
1.76 lbs. (0.8 kg) NO FOAM



Special Application Panel Frame

IP67
• DEF STAN 81-41/STANAG 4280

EXTERIOR DIMENSIONS

INTERIOR DIMENSIONS

LID/BOTTOM DEPTH

WEIGHT

COLORS

AVAILABLE ACCESSORIES

CERTIFICATES

[LINK >](#)



1170 CASE

11.64" x 8.34" x 3.78"
(29.6 x 21.2 x 9.6 cm)

10.54" x 6.04" x 3.16"
(26.8 x 15.3 x 8 cm)

1.08" / 2.08"
(2.7 cm / 5.3 cm)

2.10 lbs. (0.95 kg) WITH FOAM
1.96 lbs. (0.89 kg) NO FOAM



IP67

1120 CASE

8.12" x 6.56" x 3.56"
(20.6 x 16.7 x 9 cm)

7.25" x 4.75" x 3.06"
(18.4 x 12.1 x 7.8 cm)

0.50" / 2.56"
(1.3 cm / 6.5 cm)

1.23 lbs. (0.56 kg) WITH FOAM
1.17 lbs. (0.53 kg) NO FOAM



Special Application Panel Frame

IP67
• DEF STAN 81-41/STANAG 4280



[LINK >](#)

EXTERIOR DIMENSIONS

INTERIOR DIMENSIONS

LID/BOTTOM DEPTH

WEIGHT

COLORS

AVAILABLE ACCESSORIES

CERTIFICATES

[LINK >](#)

Similarly sized Pelican™ Storm Case™: iM2050



1200 CASE

10.62" x 9.68" x 4.87"
(27 x 24.6 x 12.4 cm)

9.25" x 7.12" x 4.12"
(23.5 x 18.1 x 10.5 cm)

1.18" / 2.93"
(3 cm / 7.4 cm)

2.87 lbs. (1.3 kg) WITH FOAM
2.65 lbs. (1.2 kg) NO FOAM



Special Application Panel Frame

IP67
• DEF STAN 81-41/STANAG 4280

Similarly sized Pelican™ Storm Case™: iM2075

1300 CASE

Similarly sized Pelican™ Storm Case™: iM2100

1400 CASE



> Shown with panel frame option for special application usage.

[LINK >](#)

10.62" x 9.68" x 6.87" (27 x 24.6 x 17.4 cm)	EXTERIOR DIMENSIONS
9.87" x 7.00" x 6.12" (25.1 x 17.8 x 15.5 cm)	INTERIOR DIMENSIONS
1.18" / 4.93" (3 cm / 12.5 cm)	LID/BOTTOM DEPTH
3.53 lbs. (1.6 kg) WITH FOAM 3.09 lbs. (1.4 kg) NO FOAM	WEIGHT
■ ■ ■ ■ ■ *	COLORS
Special Application Panel Frame	AVAILABLE ACCESSORIES
IP67 • DEF STAN 81-41/STANAG 4280	CERTIFICATES



[LINK >](#)

13.37" x 11.62" x 6.00" (33.9 x 29.5 x 15.2 cm)	EXTERIOR DIMENSIONS
11.81" x 8.87" x 5.18" (30 x 22.5 x 13.2 cm)	INTERIOR DIMENSIONS
1.18" / 4.00" (3 cm / 10.2 cm)	LID/BOTTOM DEPTH
4.41 lbs. (2 kg) WITH FOAM 3.97 lbs. (1.8 kg) NO FOAM	WEIGHT
■ ■ ■ ■ ■ *	COLORS
Special Application Panel Frame	AVAILABLE ACCESSORIES
IP67 • MIL C-4150J • DEF STAN 81-41/STANAG 4280 • ATA 300	CERTIFICATES

Photo by Marek Arcimowicz

